



6448

BOARD DIPLOMA EXAMINATION, (C-16)

MARCH / APRIL — 2021

DME — FOURTH SEMESTER EXAMINATION

THERMAL ENGINEERING - II

Time : Three Hours]

[Maximum Marks : 80

PART-A

3×10=30

Instructions :

- (i) Answer **all** questions.
- (ii) Each question carries **three** marks.
- (iii) Answers should be brief and straight to the point and shall not exceed *five* simple sentences.

1. A container contains 5 kg of wet steam at a pressure of 8 bar. If it is 10% wet, calculate the volume of the container.
2. Write at least six differences between fire tube boilers and water tube boilers.
3. 4 kg of steam 95% dry expands adiabatically from 1.1 MPa to 0.12 MPa. Determine using steam tables the final quality of steam.
4. 5 kg of dry and saturated steam at a pressure of 14 bar expands to 1.4 bar. Find the quality of steam at the end of expansion if the index of expansion is 1.3.
5. Superheated steam enters a convergent-divergent nozzle at a velocity of 80 m/s and with a mass flow rate of 0.8 kg/s. The pressure and temperature of the steam at the entry of the nozzle are 20 bar and 300° C and the condition at the exit is 2 bar and 10% wet. Determine the exit velocity of the steam.
6. Write at least six differences between Impulse Turbines and Reaction Turbines.

7. What are jet condensers and surface condensers ?
- *8. Write the applications of gas turbines.
9. List out the applications of Rocket engines.
10. What are the characteristics of an automobile clutch ?

PART-B

10×5=50

- Instructions :**
- (i) Answer any **five** questions.
 - (ii) Each question carries **ten** marks.
 - (iii) Answers should be comprehensive and the criterion for valuation is the content but not the length of the answer.

11. A shell of 150 litres capacity contains steam at a pressure of 15 bar and the steam is 10% wet. Calculate :

- (a) Mass of steam
- (b) Total entropy
- (c) Heat required to superheat it to 375° C at the above pressure.

12. Describe the construction and working principle of Cochran boiler with a neat sketch.

13. A vessel of 1200 litres capacity contains steam at a pressure of 18 bar and at a temperature of 270° C. It is expanded to a pressure of 1.4 bar according to $PV^{1.3} = \text{constant}$. Determine :

- (a) The final condition of steam
- (b) The total change in internal energy
- (c) Total work done
- (d) The total change in entropy

* 14. A convergent-divergent nozzle receives wet steam of 2% wet at a pressure of 26 bar with an approach velocity of 100 m/s and expands it to a back pressure of 0.3 bar. Nozzle efficiency is 85% and all the frictional losses take place in the divergent portion only. Determine :

- (a) The critical throat pressure
- (b) The discharge of steam
- * (c) The area of cross section of the nozzle at its exit

15. In an impulse turbine the nozzles are inclined at 18° to the wheel tangent. Steam leaves the nozzles at 800 m/s with a flow rate of 10 kg/s. The blade speed is 280 m/s. The relative velocity of steam as it flows over the blades is reduced by 10% due to friction. Determine :

- (a) The suitable inlet and outlet angles for the blades to ensure the axial thrust to be zero
- (b) Work done
- (c) Power developed
- (d) Diagram efficiency.

16. Explain with a neat sketch the working principle of constant volume gas turbine.

17. Write the working principle of RAM jet engine with a neat diagram.

18. Explain the working principle of multi plate clutch.

* * * * *